



Features



- High quality vacuum fluorescent customer display 20 columns x 2 lines by 5 x7 font
- High brightness and speedy display response- Easy to read
- Wide viewing angle-vertical range 45°; Horizontal range 125°
- Multiple languages supported-Built-in 12 international fonts
- Wide temperature-Range from -40°C to +80°C
- Adjustable pole-Easy to set up
- ESC/POS and 10 other commands supported
- OPOS driver supported

Specifications

Model	MP-4003
Customer Display	Vacuum fluorescent display blue green
Interface	RS232
Display Pattern	5 x 7 dot matrix
Character	95 alphanumeric & 32 international characters
Dot size (X x Y)	0.85 x 1.05 mm
Font size	5.25 (W) x 9.03 (H)
Character Number	20 x 2 for 5 x 7 font
Dimensions (Panel)	217.3 x 44.6 x 63.4 mm (WxDxH)
Dimensions (Support)	Adjustable pole Max Length= 280.5 mm; min Length=155.5 mm
Dimensions (Base)	145.2 mm (W) x 90.0 mm (D) x 32.0 (H) mm
Viewing Angle	Max. 45°
Horizontal Rotation	Max. 125°
Language	US English, French, German, Swedish, Danish, Spanish, Norwegian, Japanese (Katakana), Russian ... etc.

*All information contained in this document is subject to change without prior notice. Please log on www.protech.com.tw to acquire latest information.

www.protech.com.tw