

MP-4815 Stand-alone Display



NEW



Features

- Ultra-thin LCD panel
- 15" backlight LCD display
- IP54 front display
- On-screen display easy to use
- Support resistive & PCAP touch

Optional

- 5M pixel USB camera module
- 2D barcode scanner module
- MSR / RFID / Fingerprint USB interface

Specifications



| | |
|---------------------------|--|
| Model | MP-4815 |
| Customer (2nd) Display | 15" XGA LCD (250 cd/m ²) |
| Display Resolution | 1024 x 768 (XGA) |
| Font Size | 367(W) x 37.8 mm |
| Dimension (Panel) (WxDxH) | 367 x 299.3 x 37.8 mm |
| Viewing Angle | Horizontal 80°, Vertical 70° |
| Optional | Max. 4-USB device support |
| I/O Ports | VGA DVI-I cable (support DVI-D signal only) USB |
| Language | English, French, Deutsch, Italiano, Spanish, Japanese, Chinese (Traditional) |
| Power Supply | DC12V Power Jack (9-16V power input) |
| Environment | EMC & Safety: CE Operating Temp: 0°C ~ 40°C Storage Temp: -20°C ~ 60°C Humidity: 20 ~ 90% |

*All information contained in this document is subject to change without prior notice. Please log on www.protech.com.tw to acquire latest information.

MP-4815 Stand-alone Display



Ordering Information

| Order No | Description |
|---|--|
| MP-4815RA-21B + MP-4815RZ-PP1 + 90-021-10150393 + 90-021-10550393 + MP-4815RZ-ST1 | Stand-alone Module only with Easy-Stand |
| MP-4815RA-21B + MP-4815RZ-RT2 + MP-4815RZ-ST1 | ABON RT-Touch Stand-alone Module with Easy-Stand |
| MP-4815RA-21B + MP-4815RZ-PT1 + MP-4815RZ-ST1 | GTOC PCAP-Touch Stand-alone Module with Easy-Stand |
| MP-4815RA-21B + MP-4815RZ-PP1 + 90-021-10150393 + 90-021-10550393 + MP-4815RZ-ST2 | Stand-alone Module with Normal-Stand |
| MP-4815RA-21B + MP-4815RZ-RT2 + MP-4815RZ-ST2 | ABON RT-Touch Stand-alone Module with Normal-Stand |

Ordering Information




| Order No | Description |
|---|--|
| MP-4815RA-21B + MP-4815RZ-PT1 + MP-4815RZ-ST2 | GTOC PCAP-Touch Stand-alone Module with Normal-Stand |
| MP-4815RZ-CC1 | PPC Cable Cover package |
| MP-4815RZ-CM1 | Camera Module packing |
| MP-4815RZ-BS1 | Barcode Scanner packing |
| MP-4815RZ-RF1 | Vertical RFID only, 13.56MHz, Mifare (UID, Read, Write) |
| MP-4815RZ-RM1 | Vertical RFID, 13.56MHz, Mifare (UID, Read, Write) + MSR Module, ISO, JIS1,2 |
| MP-4815RZ-MS1 | MSR, black, ID-Tech, ISO I /II /III , USB |
| MP-4815RZ-FP1 | Fingerprint kit, need to match the amount of MSR orders |
| MP-4815RZ-FP2 | Fingerprint kit, single type |

Applications




- Food service
- Retail
- Hospitality

Dimensions

Easy Stand



Normal Stand



unit: mm